

AkyLite[®]

Ideal for short term advertising, **AkyLite** is easy to convert & fully recyclable

Benefits



100% recyclable



Flat, uniform surface



Easy to convert



Lightweight



Weather resistant



Customizable treatments




Bubble Structure Sheets

- **Dimensions:**

Sheets from 2,5mm – 450g/m² to 2,9mm 600g/m²

Printing



Silk-screen



Inkjet Digital



1 sided



Offset

Applications

- Short term advertising
- Displays
- Elections panels
- Promotional sales

Products line & Specifications

Standard products				Sustainability		Treatments*		Printing					
Quality	Structure	Thickness	gr/m²	3R	Circular	UV	Fire retardant	Silk-screen		Digital		Offset	
								1 sided	2 sided	1 sided	2 sided	1 sided	2 sided
AkyPrint®	Bubble	3mm	750gr	●		●		●	●	●	●		
		3.3mm	900gr	●		●	▲	●	●	●	●		
		4mm	1300gr			●	▲	●	●	●	●		
		5mm	1300gr	●		●		●	●	●	●		
		5.4mm	1600gr	●		●	▲	●	●	●	●		
		9.2mm	2000gr			●		●	●	●	●		
		9.6mm	2600gr			●		●	●	●	●		
AkyPrint® BLACK		4mm	1300gr			●		●	●	●	●		
AkyLite®	Bubble	2.5mm	450gr	●		▲		●		●			
		2.9mm	600gr	●		▲	▲	●		●			
AkyPlac®	Fluted	3 to 10mm	450gr - 1800gr		●	▲	only 10mm/1800gr	●	●	●	●		
AkyPlen®	Solid	0.3 to 2mm	gloss, sand, quartz		●	▲		●	●	●	●	●	●
AkyPlen® Rigid		0.4 to 0.5mm	gloss, sand, quartz			▲		●	●	●	●	●	●

*UV and fire retardant treatments cannot be applied on the same sheet.
All our sheets are white (except AkyPrint® Black).
Other colors are available on request.

● available

▲ on option

Fire certifications

AkyLite[®]

- 2,9 mm 600g/m²
B1 certified

AkyPrint[®]

- 3,3 mm 900g/m²
B, s1-d0 + B1 certified
- 3,3 mm 900g/m² **3R** (black core)
B, s1-d0
- 4,0mm 1300g/m²
B1 certified
- 5,4mm 1600g/m²
B1 certified
- 5,4mm 1600g/m² **3R** (black core)
B1 certified

AkyPlen[®]

- 1,2 mm - Translucent / non-slip
M2 certified
- 0,7 mm Black
B2 certified

AkyPlac[®]

- 10 mm 1800g/m²
B1 certified



**Please ask us for new
certifications needs**