

**POLI-TAPE®**



# ***TURBO* SEC** ***PRINT***

MOVE WITH THE  CHANGING TIMES



POLI-TAPE Klebefolien GmbH  
Zeppelinstraße 17  
53424 Remagen - GERMANY



Phone: +49 2642 98 36 0  
Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Web: [www.poli-tape.de](http://www.poli-tape.de)

# TURBO<sup>5</sup> SEC PRINT 4046 NON ADHESIVE

For you, POLI-TAPE combines the best of its technologies: the unique TURBO® hot-melt, an in-house casted polyurethane film with an excellent printability on eco-solvent, solvent and latex printers, a NON-ADHESIVE LINER for very easy handling. Quality Made in Germany, Made by POLI-TAPE!

## ▶ TURBO® PRINT 4046 ONLY 5 SEC. 130°C

- Enjoy the blockout properties of the flex film
  - Save electricity: With standard flex films you'd spend up to 50% more energy
  - Save time: pressing time 3 times faster than a standard flex, hot peel, no need for post-pressing, isn't that a game changer?
  - Protect your fabrics: less thermal stress, no scorch or pressure marks
- Allows a very fluid workflow, chose your parameters according to the job 130 °C, 5 sec. / 150 °C, 4 sec. / 160 °C, 3 sec.
  - No need to constantly change the settings of your transfer press
  - Intricated designs can be easily reverse weeded on the POLI-TACK 870 transfer tape
  - Also available in 60 colours for CAD and as a EN 20471 certified reflective quality with REFLEX®

## ▶ THE MOST VERSATILE

- Suitable for almost all textiles: Cotton, Polyester, Poly/Cotton, Nylons\*, Sensitive fabrics\*
- Blockout characteristics for sublimated textiles

## ▶ THE BEST FINISH

- Unique feel and matte finish
- Excellent opacity and elasticity

\*We always recommend a suitability test



100 µm



ECO-SOLVANT  
LATEX  
UV



130°C / 5 SEC  
150°C / 4 SEC  
160°C / 3 SEC



GOOD STRETCH  
PROPERTIES



60°C  
TUMBLE DRY  
DRY-CLEANING



EASY TO CUT



WARM  
LUKE WARM



2,5 - 3,0 BAR  
MEDIUM PRESSURE



OEKO  
TEX®  
STANDARD  
100  
022-2125  
Hohenstein (IT)

